

With a 32 bit RISC CPU, 6ips print speed, up to 600dpi resolution printing capability, high speed interfaces, including wireless connectivity, the CT4i series is a powerful performer in a compact design. The CT4i series is perfect for environments where space is a constraint. Its anti-microbial casing makes it most suitable for use in the healthcare environment where cleanliness and hygiene are factors that should not be compromised on.

The HF RFID option will help meet much-needed applications requirements for compact RFID printing solutions.



Features & Benefits

- Direct Thermal / Thermal Transfer Desktop Label Printer
- Prints; labels, receipts, tags & wristbands - ideal for a wide range of applications
- Anti-microbial casing - for medical/hospital applications
- Ergonomically designed - for user friendly operation & maintenance
- 203, 305 or 609 dpi resolution - suitable for standard or fine label printing
- RFID ready and upgradeable - Fully integrated Reader/encoder version available
- Fast printing speed - 100mm/sec for fast on demand labelling
- RS232C & USB (type 1), USB & LAN (type 2), Wireless LAN, Bluetooth & parallel option for type 1 - compatible with most systems

Manufactured by...



Options

- Cutter
- Dispenser
- RFID HF kit
- Wireless LAN, Bluetooth or Parallel Interface
- Smart keyboard
- Unwinder
- Rewinder
- SATO Label Gallery

Applications

Compact desktop label printers are ideal for fully or semi permanent installations including retail, industrial and office situations.

- Healthcare
- General Office
- Government
- Library
- Retail
- Logistics, transportation - address labels
- Entertainment, hospitality

Desktop Label Printer Specifications

SPECIFICATION	CT408i	CT412i	CT424i
Printing System	Direct Thermal or Thermal Transfer		
Case Colour(s)	Grey & Blue		
Cutting System	Tear bar, Autocutter & Dispenser options		
Media	Direct thermal or thermal transfer die cut labels or linerless rolls, tags and wristbands		
Media width	25-115mm		
Print Length	15 - 397mm		
Roll Diameter	110mm		
Media thickness	0.08 ~ 0.19mm		
Resolution	203 dpi 8 dots/mm	305 dpi 12 dots/mm	609 dpi 24 dots/mm
Print width	104mm		
Printing speed	up to 150mm/sec	up to 102mm/sec	up to 76mm/sec
Dimensions (WxDxH)	198 x 225 x 181mm		
Weight	3kg (excl AC adapter)		
Interfaces	Type 1: RS232C & USB (Wireless LAN, Bluetooth & parallel options) Type 2: USB & LAN		
Flow Control	Hardware or Software (XON/XOFF)		
Barcodes Supported	Most common 1D & 2D codes supported		
Power Supply	Universal Switching Power Supply Input: 100V~240V, 50~60Hz, Output: 25VDC, 2A		
Operating temp.	5 to 35°C		
Humidity	30 to 80%		

© M-Tech Printers 2013

This data sheet is for information purposes only. M-Tech Printers make no warranties, expressed or implied in this summary. Specifications are subject to change without notice. All trademarks are the property of their respective owners. For more information contact: M-Tech Printers, Telephone: +44(0)330 330 3164, email: sales@mtechprinters.co.uk, web: www.mtechprinters.co.uk